

## Low Profile BOTTLE JACKS

12, 20 & 30 Ton

The right choice for those  
lower clearance jobs.



- All the quality, features and lifting capacity of the standard jacks in short form. The 12-ton and 20-ton models feature screw extensions for added versatility.
- All jacks meet ASME B30.1 standards and carry the Power Team Marathon Lifetime Warranty.
- All jacks operate both vertically and horizontally for use in a variety of lifting, pushing and spreading applications.

### ORDERING INFORMATION\*

Cap. Tons	Stroke (in.)	Order Number	Retracted Height Min. (in.)	Length of Screw Ext. (in.)	Height w/Screw Ext. (in.)	No. Pump Strokes to Ext. Piston (in.)	Saddle Dia. (in.)	Base Size (in.)	Pump Handle Length (in.)	Handle Effort at Rated Cap. (lbs.)	Carry Handle	Product Weight (lbs.)
12	3 <sup>3</sup> / <sub>4</sub>	<b>9012A</b>	6 <sup>3</sup> / <sub>4</sub>	3	13 <sup>1</sup> / <sub>2</sub>	26	1 <sup>7</sup> / <sub>8</sub>	6 <sup>1</sup> / <sub>2</sub> x 4 <sup>3</sup> / <sub>16</sub>	23 <sup>13</sup> / <sub>16</sub>	60	Yes	14
20	3 <sup>3</sup> / <sub>8</sub>	<b>9020A</b>	7 <sup>1</sup> / <sub>8</sub>	1 <sup>3</sup> / <sub>16</sub>	12	22	2	7 <sup>3</sup> / <sub>16</sub> x 5 <sup>1</sup> / <sub>16</sub>	31 <sup>1</sup> / <sub>2</sub>	70	Yes	22.2
30	3 <sup>1</sup> / <sub>8</sub>	<b>9130A</b>	7 <sup>1</sup> / <sub>8</sub>	—	10 <sup>1</sup> / <sub>4</sub>	35	2 <sup>3</sup> / <sub>8</sub>	7 <sup>9</sup> / <sub>16</sub> x 5 <sup>9</sup> / <sub>16</sub>	39 <sup>3</sup> / <sub>8</sub>	50	Yes	30.2

\* See current price list for shipping weights.

† 2 Speed: Rapid advance≈40 strokes; Lift mode≈160 strokes

JACKS