

recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

#### Health and Safety

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.



cutting oil for all types of steel

Bio-Cut contains no mineral oil, has water pollutant class 1 as a self-classification according to VwVwS (Verwaltungs-vor-schrift wassergefährdende Stoffe = German Administrative Regulation Regarding Water Pollutants), and is easily biodegradable.

Thanks to its particularly high lubricating effect, WEICON Bio-Cut enables high cutting speeds, long tool lives and thus also high tool cutting performance.

WEICON Bio-Cut can be used for drilling, turning, milling, grinding, sawing, punching and Thread cutting of all types of steel, castings, stainless steel, copper, brass, aluminium, and their alloys in all industrial applications.

#### Technical data

|                        |  |
|------------------------|--|
| Colour                 | clear                                  |
| Odour                  | almost odourless                       |
| Temperature resistance | bis +200 °C                            |
| Shelf life min.        | 24 months                              |
| Special features       | mineral oil-free, easily biodegradable |
| Suitable for use with  | WSD 400                                |

#### Processing

Richly apply Bio-Cut undiluted on the work piece by brushing, dropping or spraying (e.g. with an Air Pressure Can).

#### Storage

Keep in closed original container. Protect from direct solar radiation. Storage temperature may not exceed +50 °C. Store container at cool and aired place. Store in a dry place.

#### Note

Any product specifications and recommendations given herein must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do warrant the continuously high quality of our products being free from defects in accordance with and subject to our General Sales Conditions. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are

#### WEICON GmbH & Co. KG (Headquarter)

Königsberger Str. 255 · DE-48157 Münster  
P.O. Box 84 60 · DE-48045 Münster  
Germany

Tel. +49 (0) 251 / 93 22-0  
Fax +49 (0) 251 / 93 22-244  
Fax +49 (0) 251 / 93 22-233 Export  
[www.weicon.de](http://www.weicon.de) · [info@weicon.de](mailto:info@weicon.de)

#### WEICON Middle East L.L.C.

Jebel Ali Ind Area 3 · P.O. Box 118 216  
Dubai · U.A.E

Phone +971 4 880 25 05  
Fax +971 4 880 25 09  
Mobile +971 50 545 99 83  
[www.weicon.ae](http://www.weicon.ae) · [info@weicon.ae](mailto:info@weicon.ae)

#### WEICON Inc.

20 Steckle Place · Unit 20  
Kitchener · Ontario · N2E 2C3  
Canada

Phone +1 519 896 5252  
Fax +1 519 896 5254  
Cell +1 519 590 5168  
[www.weicon.ca](http://www.weicon.ca) · [info@weicon.ca](mailto:info@weicon.ca)

#### WEICON Kimya Sanayi Tic. Ltd. Şti.

Yenibosna Mahallesi Yalçın Koreş Caddesi  
Arifağa Sokak No: 29 Kat: 3  
34530 Yenibosna – İstanbul Turkey  
[www.weicon.biz.tr](http://www.weicon.biz.tr) · [info@weicon.biz.tr](mailto:info@weicon.biz.tr)

#### WEICON Romania SRL

Str. Podului Nr.1  
547176 Budiu Mic (Targu Mures)  
[www.weicon.com](http://www.weicon.com) · [office@weicon.com](mailto:office@weicon.com)